



CARRETE DESMONTAJE PN10/16/25 DOBLE BRIDA

DISMANTLING JOINT PN10/16/25 FLANGED

Fig. 6420

Características / Features

Bridas / Flanged	PN10/16/25
Presión nominal / Nominal pressure	10-16-25 bar
Test presión / Pressure test	15/24/37,5 bar
Recubrimiento / Coating	Resina epoxi fundida / Fusion epoxi coated

Materiales / Materials

Descripción / Part name	Material
Virola / Pipe	AISI304/316/316L
Bridas / Flanged	Ac. Carbono. Carbon Steel/AISI304/316/316L
Junta / Gasket	Nitrilo/EPDM
Tornillos brida de apriete / Clamping flange bolts	Acero Dicromatizado/Acero Inox / Dicromatized steel/Stainless steel

Dimensiones / Main dimensions

Tamaño / Size		L	L1	L2
DN	NPS			
50	2"	150	180	210
65	2½"	150	180	210
80	3"	150	180	210
100	4"	150	180	210
125	5"	150	180	210
150	6"	150	180	210
200	8"	160	200	240
250	10"	160	200	240
300	12"	160	200	240
350	14"	200	240	280
400	16"	200	240	280
450	18"	200	240	280
500	20"	200	240	280
600	24"	260	300	340
700	28"	260	300	340
800	32"	260	300	340
900	36"	260	300	340
1000	40"	260	300	340
1100	44"	260	300	340
1200	48"	260	300	340

