



FILTRO EN "Y" PN16 BRIDAS DIN

"Y" STRAINER PN16 DIN FLANGED

Fig. 7110

Características / Features

Diseño / Design	Filtro en Y. Tapa atornillada / Y pattern. Bolted bonnet
Rating	PN16
Distancia entre caras / Face to face	DIN 3202 F1
Extremos / Ends	Bridas DIN / DIN Flanged

Materiales / Materials

N°	Descripción / Part name	Material
1	Cuerpo / Body	GG22 / GG25 / A216 WCB / A351 CF8M
2	Junta / Gasket	AISI 304 + Grafito / EPDM / NBR
3	Tamiz / Screen	AISI 304 / AISI 316

Dimensiones / Main dimensions

Tamaño / Size		L	H	D	D1	D2	n-ød	Peso / Weight Kg
DN	NPS							
15	½"	130	65	95	65	46	4-14	2,0
20	¾"	150	70	105	75	56	4-14	2,3
25	1"	160	80	115	85	65	4-14	3,2
32	1¼"	180	90	140	100	76	4-19	5,0
40	1½"	200	135	150	110	84	4-19	6,5
50	2"	230	150	165	125	99	4-19	8,7
65	2½"	290	160	185	145	118	4-19	12,0
80	3"	310	200	200	160	132	8-19	19,0
100	4"	350	240	220	180	156	8-19	27,0
125	5"	400	290	250	210	184	8-19	40,0
150	6"	480	330	285	240	211	8-23	58,0
200	8"	600	380	340	295	266	12-23	86,0
250	10"	730	480	405	355	319	12-28	127,0
300	12"	850	550	460	410	370	12-28	200,0
350	14"	980	680	520	470	429	16-28	320,0
400	16"	1100	780	580	525	480	16-31	420,0
450	18"	1200	830	640	585	548	20-31	620,0
500	20"	1250	910	715	650	609	20-34	780,0

