



VÁLVULA DE BOLA SOLDADA CON VENTEOS 150#/300#/600# BW

BALL VALVE FULLY WELDED WITH VENTS 150#/300#/600# BW

Fig. 5192

Características / Features

Diseño / Design	API 6D. 1 pieza soldada. Paso reducido. Con venteos / API6D. 1 welded piece. Reduced bore. With vent valves
Rating	150#/300#/600#
Distancia entre caras / Face to face	ASME B16.10
Extremos / Ends	BW

Materiales / Materials

Descripción / Part name	Material
Cuerpo / Body	A105
Bola / Ball	ASTM A351 CF8M
Eje / Stem	AISI 316
Asiento / Seat	RPTFE

Dimensiones / Main dimensions

Tamaño / Size		L	D	C	d	H	F
DN	NPS						
100	4"	905	200x200	120	124	1100	400
150	6"	1003	230x230	145	176	1100	460
200	8"	1102	260x260	160	231	1100	540
250	10"	1168	290x290	175	285	1200	590
300	12"	1248	320x320	190	335	1200	650
350	14"	1962	350x350	200	373	1200	700
400	16"	2038	380x380	220	424	1300	760
450	18"	2114	420x420	235	475	1300	820
500	20"	2191	450x450	250	526	1300	900

