



VÁLVULA DE COMPUERTA ASIENTO ELÁSTICO HUSILLO INTERIOR PN16 EXTREMOS SOCKET

RESILIENT SEATED GATE VALVE INSIDE SCREW PN16 SOCKET ENDS

Fig. 5223

Características / Features

Diseño / Design	DIN 3352. Tapa atomillada. Husillo interior. Cierre elástico / DIN 3352. Bolted bonnet. Non rising stem. Resilient seated
Rating	PN16
Distancia entre caras / Face to face	DIN 3202-F5
Extremos / Ends	Socket

Materiales / Materials

N°	Descripción / Part name	Material
1	Cuerpo / Body	GGG50
2	Cuña / Wedge	GGG50 + EPDM / GGG50 + NBR
3	Eje / Stem	AISI 420
4	Junta / Gasket	EPDM / NBR

Dimensiones / Main dimensions

Tamaño / Size		D	L	L1	H	Peso / Weight Kg
DN	NPS					
50	2"	63	250	77	300	7,15
65	2½"	75	270	80	310	8,25
80	3"	90	280	84	350	12,65
100	4"	110	300	88	380	18,70
125	5"	125	325	91	420	23,10
		140	325	91	420	24,20
150	6"	160	350	94	470	33,00
		200	400	100	590	45,10
200	8"	225	400	100	590	47,30
		250	450	125	680	67,10
300	12"	315	500	140	790	92,40

