



Fig. 5220

# VÁLVULA DE COMPUERTA CIERRE ELÁSTICO HUSILLO INTERIOR PN10/16 BRIDAS DIN

## RESILIENT SEATED GATE VALVE NON RISING STEM PN10/16 DIN FLANGED

### Características / Features

|   |   |
|---|---|
| Diseño / Design                         | DIN 3352. Tapa atornillada. Husillo interior. Cierre elástico /<br>DIN 3352. Bolted bonnet. Non rising stem. Resilient seated |
| Rating                                  | PN10/16   |
| Distancia entre caras /<br>Face to face | DIN 3202-F4   |
| Extremos / Ends                         | Bridas DIN / DIN Flanged  |

### Materiales / Materials

| N° | Descripción / Part name | Material     |
|----|-------------------------|--------------|
| 1  | Cuerpo / Body           | GGG50        |
| 2  | Cuña / Wedge            | GGG50 + EPDM |
| 3  | Eje / Stem              | AISI 420     |
| 4  | Junta / Gasket          | EPDM         |

### Dimensiones / Main dimensions

| Tamaño / Size |     | H    | L   | D    |      | D2   |      | D1   |      | n-ød        |      | Peso / Weight<br>Kg |
|---------------|-----|------|-----|------|------|------|------|------|------|-------------|------|---------------------|
| DN            | NPS |      |     | PN10 | PN16 | PN10 | PN16 | PN10 | PN16 | PN10        | PN16 |                     |
| 40            | 1½" | 198  | 140 | 150  | 110  | 84   |      |      |      | 4-19        | 9    |                     |
| 50            | 2"  | 216  | 150 | 165  | 125  | 99   |      |      |      | 4-19        | 11   |                     |
| 65            | 2½" | 260  | 170 | 185  | 145  | 118  |      |      |      | 4-19        | 14   |                     |
| 80            | 3"  | 286  | 180 | 200  | 160  | 132  |      |      |      | 8-19        | 17   |                     |
| 100           | 4"  | 325  | 190 | 220  | 180  | 156  |      |      |      | 8-19        | 21   |                     |
| 125           | 5"  | 389  | 200 | 250  | 210  | 184  |      |      |      | 8-19        | 29   |                     |
| 150           | 6"  | 428  | 210 | 285  | 240  | 211  |      |      |      | 8-23        | 38   |                     |
| 200           | 8"  | 532  | 230 | 340  | 295  | 266  |      |      |      | 8-23 12-23  | 58   |                     |
| 250           | 10" | 636  | 250 | 395  | 405  | 350  | 355  | 319  |      | 12-23 12-28 | 90   |                     |
| 300           | 12" | 744  | 270 | 445  | 460  | 400  | 410  | 370  |      | 12-23 12-28 | 120  |                     |
| 350           | 14" | 840  | 290 | 505  | 520  | 460  | 470  | 429  |      | 16-23 16-28 | 180  |                     |
| 400           | 16" | 970  | 310 | 565  | 580  | 515  | 525  | 480  | 489  | 16-28 16-31 | 235  |                     |
| 450           | 18" | 1045 | 330 | 615  | 640  | 565  | 585  | 530  | 548  | 20-28 20-31 | 345  |                     |
| 500           | 25" | 1150 | 350 | 670  | 715  | 620  | 650  | 582  | 609  | 20-28 20-34 | 415  |                     |
| 600           | 24" | 1295 | 390 | 780  | 840  | 725  | 770  | 682  | 720  | 20-31 20-37 | 575  |                     |

