

VÁLVULA DE COMPUERTA HUSILLO INTERIOR PN10 BRIDAS DIN

GATE VALVE NON RISING STEM PN10 DIN FLANGED



Fig. 5202

Características / Features

Diseño / Design	DIN 3352. Tapa atornillada. Husillo interior. Cierre metal-metal / Bolted bonnet non rising stem metal-metal seat
Rating	PN10
Distancia entre caras / Face to face	DIN 3202-F4
Extremos / Ends	Bridas DIN / DIN Flanged

Materiales / Materials

Nº	Descripción / Part name	Material
1	Cuerpo / Body	GG25
2	Asiento / Seat	Latón / Brass - AISI304L
3	Cuña / Wedge	GG25
4	Eje / Stem	AISI 420
5	Junta / Gasket	Cartón / Cellulose

Dimensiones / Main dimensions

Tamaño / Size		D1	D2	D	L	H	n-ød	Peso / Weight Kg
DN	NPS							
40	1½	88	110	150	140	250	4-ø18	11
50	2	102	125	165	150	270	4-ø18	12
65	2½	122	145	185	170	310	4-ø18	16
80	3	138	160	200	180	335	8-ø18	19
100	4	158	180	220	190	385	8-ø18	26
125	5	188	210	250	200	445	8-ø18	36
150	6	212	240	285	210	480	8-ø23	51
200	8	268	295	340	230	610	8-ø23	62
250	10	320	350	395	250	740	12-ø23	127
300	12	378	400	445	270	800	12-ø23	165
350	14	378	460	505	290	880	16-ø23	225
400	16	378	515	565	310	980	16-ø28	369

