

# VÁLVULA DE RETENCIÓN A CLAPETA PN16 BRIDAS DIN

## SWING CHECK VALVE PN16 DIN FLANGED



Fig. 5411

### Características / Features

Rating	PN16
Distancia entre caras / Face to face	DIN 3202 F6
Extremos / Ends	Bridas DIN / Din Flanged

### Materiales / Materials

N°	Descripción / Part name	Material
1	Cuerpo / Body	GG25 / GGG50 / A216 WCB / A351 CF8M
2	Asiento / Seat	Brass / NBR / EPDM / A182 F6A + STL
3	Clapeta / Disc	GG25 / GGG50 / A216 WCB + 13% Cr / ASTM A351 CF8M
4	Junta / Gasket	AISI 304 + Grafito / AISI 316 + Graphite

### Dimensiones / Main dimensions

Tamaño / Size		L	D	D1	D2	n-ød	H	Peso / Weight Kg
DN	NPS							
40	1½"	180	150	110	84	4-18	110	9
50	2"	200	165	125	102	4-18	120	13,4
65	2½"	240	185	145	122	4-18	135	17,7
80	3"	260	200	160	138	8-18	148	20,8
100	4"	300	220	180	156	8-18	180	29,3
125	5"	350	250	210	188	8-18	205	47
150	6"	400	285	240	212	8-23	230	67
200	8"	500	340	295	268	12-23	258	118,7
250	10"	600	405	355	320	12-27	391	171,9
300	12"	700	460	410	378	12-27	427	232,5
350	14"	800	520	470	438	16-27	561	330
400	16"	900	580	525	490	16-30	582	460
500	20"	1100	715	650	610	20-34	561	700
600	24"	1300	840	770	725	20-37	582	780

