

# VÁLVULA DE SEGURIDAD COMPACTA PN10 CLAMP-CLAMP / CLAMP-ROSCA GAS COMPACT SAFETY VALVE PN10 CLAMP-CLAMP / CLAMP-GAS THREADED



Fig. 6107

## Características / Features

Diseño / Design	EN-12516-1, EN-4126-1/7
Rating	PN10
Distancia entre caras / Face to face	Según tabla de dimensiones / According to dimension table
Extremos / Ends	Clamp / Gas

## Materiales / Materials

N°	Descripción / Part name	Material
1	Cuerpo / Body	AISI CF3M
2	Tobera / Nozzle	AISI 316L
3	Obturador / Disc	AISI 316L
4	Muelle / Spring	AISI 302

## Dimensiones / Main dimensions

Entrada / Inlet	Salida / Outlet	Orificio / Orifice	Área (mm <sup>2</sup> )	L (mm)	H1 (mm)	H2 (mm)	Peso / Weight Kg
15	25	9,5	71	66	68	155	2,4
20	25	15	176,6	66	68	155	2,4
25	25	18	254	66	73	155	2,8
40	10	32	804	90	98	234	8,2
15	1"	9,5	71	45	68	155	2
20	1"	15	176,6	45	68	155	2
25	1"	18	254	45	68	155	2,2
40	2"	32	804	62	98	234	8,2

